

NewsPress

by Stora Enso



NewsPress is a standard newsprint grade. It is available with several combinations of recycled and primary fibre.

- Outstanding runnability
- Excellent in four colour printing
- Produced according to Ifra standard

PRODUCER
Langerbrugge Mill

TYPICAL END USES

Newspapers
Supplements
Free sheets

CHARACTERIZATION DATA

WAN-IFRA

| L* a* b* target values | L* | a* | b* | Flourescence (ISO 12647-2) |
|------------------------|----|----|----|----------------------------|
| ISO 13655 (D50/2°) | 82 | 0 | 3 | Faint |

PRINTING METHODS

CSWO
(HSWO)

ICC-PROFILE

Download: [Technical Resource Centre](#)

TECHNICAL SPECIFICATIONS - 100 % recycled fibre (target values)

| Substance | ISO 536 | g/m ² | 40 | 42 | 42.5 | 45 | 48.8 |
|------------|----------------------|------------------|-----|-----|------|-----|------|
| Brightness | ISO 2470-1 (C/2°) | % | 57 | 57 | 57 | 57 | 57 |
| Opacity | ISO 2471 | % | 92 | 93 | 93 | 94 | 95 |
| Thickness | ISO 534 | µm | 59 | 62 | 62 | 64 | 68 |
| Smoothness | PPS 1MPa, ISO 8971-4 | µm | 4.3 | 4.3 | 4.3 | 4.3 | 4.3 |
| Roughness | Bendtsen ISO 8791-2 | ml/min | 170 | 170 | 170 | 170 | 170 |

REEL SPECIFICATIONS

Core: 76 mm/150 mm
Diameters: min. 1000, max. 1500 mm

Max trimmed width:
1036/1037 cm

CERTIFICATES

Quality ISO 9001
Environment ISO 14001
Health & Safety ISO 45001
Energy ISO 50001
Blue Angel UZ 14a 38125
[FSC Mix Credit / FSC Recycled](#)
[INS-COC-100054](#)
[100 % PEFC certified 8949-06](#)
For more information:
www.storaenso.com/paper-sustainability

ENVIRONMENT

Renewable fibre
Recyclable paper
Recyclable packaging materials

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.